

RIM MAXIMUM PRESSURE RATING CHART

Tire Width ¹		Clincher Rim Internal Width ²					Rim maximum pressure rating ³	
(mm)	(inch)	23 - 26mm	27 - 29mm	30 - 34mm	35 - 38mm	39 - 45mm	(bar)	(psi)
38	1.5	●					4.5	66
42	1.7	●					4.1	60
44	1.8	●	●				3.9	56
48	1.9	●	●				3.6	52
51	2.0	●	●	●			3.4	49
53	2.1	●	●	●			3.2	47
57	2.25		●	●	●		3.0	44
60	2.35		●	●	●		2.9	42
61	2.4		●	●	●	●	2.8	41
64	2.5			●	●	●	2.7	39
66	2.6			●	●	●	2.6	38
69	2.7				●	●	2.5	36
71	2.8				●	●	2.3	34
74	2.9					●	2.1	31
76	3.0					●	2.0	29

● Permitted Combination (also check with tire manufacturer for permitted rim width and type)

1. Refer to technical information on tires.

EXAMPLE: 29 x 2.25

2. Refer to technical information on Race Face rims.

EXAMPLE: 622 x 30

3. For conventional tire systems

(tubeless ready and with innertube).

The tire pressure must stay within the tire manufacturer's specified pressure, but never exceed the rim maximum pressure rating specified by Race Face.

